

Amendments to Claims:

This listing of claims will replace all prior versions and listings of the claims in the application:

Listing of Claims:

1. (currently amended) A display comprising:
 - a display unit having a display panel;
 - a first casing covering a front side of the display unit including an exposed display panel, and having a window for showing an effective image area of the display panel; and
 - a second casing connected with the first casing by a predetermined connection means so as to cover a rear side of the display unit,
 - the connection means comprising:
 - at least one first hole penetrating an outer frame of the first casing;
 - at least one fastening projection protruding from an inner wall of the second casing toward the display unit, the at least one fastening projection being spaced apart from an outer frame of the second casing, and having a fastening hole corresponding to the at least one first hole; and
 - at least one fastening member having a screw part which is screw-coupled with the fastening hole by penetrating the first hole.
2. (original) The display of claim 1, wherein a spacing is provided between an inner wall of the first casing opposing the front side of the display unit and an end of the fastening projection, with a thickness not less than a thickness of the display unit.
3. (original) The display of claim 2, wherein a rear side of the display unit is supported by a contact with a free end of the fastening projection.
4. (original) The display of claim 2, wherein a control board is disposed between the display unit and the second casing to control the display unit to reproduce an image, and

the control board comprises at least one notch unit which is cut in a predetermined shape to receive the screw part of the fastening member and the fastening projections.

5. (currently amended) The display of claim 4, wherein
the first hole is formed at an end of the outer frame of the first casing,
~~the second casing comprises an outer frame of the second casing which~~ faces the
fastening projection,
~~with the first hole is positioned therebetween the outer frame of the second casing and the~~
fastening projection, when the first and the second casings are connected, and
the outer frame of the second casing has a second hole facing the first hole.

6. (original) The display of claim 5, wherein the first and the second casings are connected so that the outer frames thereof form a plane.

7. (original) The display of claim 3, wherein the display unit is pivotally mounted at one side of the portable device body by the hinge unit, and a hinge unit connects the portable device body and the control board for mutual signal transmission.

8. (original) The display of claim 7, wherein a part of the hinge unit is fixed to an outside of at least one of the first and the second casings, and all sides of the display unit are supported by contact with the inner wall of the outer frame of the first casing.

9. (original) The display of claim 7, wherein a part of the hinge unit is fixed inside the first and the second casings, penetrating a connection hole formed at one side of the first and/or the second casings, and all sides of the display unit are supported by contact with the inner wall of the outer frame of the first casing except one side which opposes the hinge unit.

10. (original) The display of claim 9, wherein the first casing further comprises at least one block piece protruding from the inner wall to support the display unit by contact and prevent the display unit from inclining to the hinge unit.

11. (original) The display of claim 1, wherein the second casing and the fastening projection are integrally formed with each other.

12. (original) The display of claim 11, wherein the second casing and the fastening projection are made by metal molding with the metal having a predetermined hardness.

13. (currently amended) The display of claim 12, wherein
the first hole is formed at an end of the outer frame of the first casing,
the second casing comprises an outer frame of the second casing which faces the
fastening projection,
~~with the first hole is positioned therebetween~~ the outer frame of the second casing and
the fastening projection, when the first and the second casings are connected, and
the outer frame of the second casing has a second hole facing the first hole.

14. (original) The display of claim 13, wherein a center portion of the fastening projection, which faces the second hole and has a fastening hole, protrudes a predetermined length toward the second hole.

15. (original) The display of claim 5, wherein the second hole of the second casing is structured having a groove to accept a portion of the first casing having the first hole.

16. (currently amended) A display having a display unit and a control board disposed between a first casing and a second casing, the display comprises:
at least one first hole disposed on at least one edge of said first casing;
at least one second hole disposed on at least one ~~an~~ edge of said second casing;
at least one fastening projection protruding from an inner wall of the second casing
toward the display unit, the at least one fastening projection being spaced apart from the at least
one edge of said second casing disposed on an inner wall of an edge of said second casing, said

fastening projection including a fastening hole corresponding to said first hole and said second hole; and

at least one notch unit located on at least one edge of said control board.

17. (currently amended) The display of claim 2016, further comprising:
a fastening member for pivotally connecting the first casing and the second casing via said first hole, second hole and fastening hole.

18. (currently amended) The display of claim 2117, wherein said fastening member comprises a screw:

19. (currently amended) The display of claim 2016, wherein said fastening projection and said second casing are integrally formed.

20. (currently amended) The display of claim 2319, wherein said fastening projection and said second casing are formed using metal molding.

21. (currently amended) The display of claim 2016, wherein the at least one fastening projection fits within the at least one notch unit of the control board when the first casing and the second casing are in a closed state.

22. (new) The display of claim 16, wherein
the second hole of the second casing is structured having a groove to accept a portion of
the first casing having the first hole.

23. (new) The display of claim 1, wherein
the outer frame of the second casing comprises a second hole facing the first hole; and
the second hole of the second casing is structured having a groove to accept a portion of
the first casing having the first hole.